

DAFTAR PUSTAKA

- [1]. M. H. Rashid, “Power Electronics : Circuit, Devices and Applications”, Prentice Hall, 2001.
- [2]. F.L. Tofoli, D.C. Pereira, W.J. Paula, D.S.O. Júnior, “Survey on non-isolated high-voltage step-up dc–dc topologies based on the boost converter”, IET Power Electronics, Vol. 8, Iss. 10, pp. 2044-2057, 2015
- [3]. M.Z. Hossain, N.A. Rahim, J. Selvaraj, “Recent Progress and Development on Power DC-DC Converter Topology, Control, Design and Applications: A Review”, Renewable and Sustainable Energy Reviews, Vol. 81, pp. 205-230, 2018.
- [4]. A. Chub, D. Vinnikov, R. Kosenko, E. Liivik, Wide Input Voltage Range Photovoltaic with Microconverter With Reconfigurable Buck-Boost Switching Stage, IEEE Transactions on Industrial Electronics, Vol. 64, No. 7, pp. 59745983, 2017.
- [5]. S. Ding, F. Wang, A New Negative Output Buck-Boost Converter with Wide Conversion Ratio, IEEE Transactions on Industrial Electronics, Vol. 64, No. 12, pp. 9322-9333, 2017.
- [6]. Mohammad Ashari Prof., Ir., M.Eng., Ph.D., IPU. 2017. “*Desain Konverter Elektronika Daya*”. Informatika: Surabaya.
- [7]. Setiawan,Iwan.2008.”Kontrol PID untuk Proses Industri”. Jakarta : PT Media Komputindo.

- [8]. Brigitte Hauke (2009) Basic Calculation of a Boost Converter's Power Stage”, Texas Instruments, Vol. 1, No. 1, pp 1-8.
- [9]. Budi Santoso (2014) Anlisa Kelebihan Kekurangan dan Solusi”, <http://budi2one.blogspot.com>
- [10] Ali, N. (2014). A Review Of Firefly Algorithm. ARPN [28] Journal of Engineering and Applied Sciences , 1-5.
- [11] Yang, X.-S. (2010). Firefly Algorithm, Stochastic Test Functions and Design. Department of Engineering, University of Cambridge , 1-12.
- [12]Yang, X.-S. (2009). Firefly Algorithms for Multimodal Optimization. pp. 1-10.